



#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## Tutto Legno Vernice H2O

Technical Data Sheet No. 142 - Revision 1 of 22/10/2013

### CHARACTERISTICS AND FIELDS OF USE

Transparent wood finish based on acrylic dispersions, suitable for painting wooden objects indoors or outdoors. It features excellent resistance to weathering and temperature changes, and good elasticity, allowing the film to adapt to the dimensional changes of the wood.

Specially formulated for protecting outdoor wood, it enhances its beauty while maintaining its long-lasting protection. It contains no substances hazardous to health, is non-flammable, and has no unpleasant odor; therefore, it is particularly suitable for use in interior or poorly ventilated environments.

Tutto Legno H2O Vernice is available in a gloss or wax-effect version using our MAT 100 150 ml bottle (0.75 lb).



### SUBSTRATE PREPARATION AND APPLICATION

**New wood:** sand the surface and remove dust and dirt; for resinous wood, clean the surface beforehand with Nitro Thinner; Make sure the surface is dry.

**Painted wood:** Remove all traces of dust, grease, wax residue, or old paint. Sand the surface and clean it of dust and dirt. For resinous wood, clean the surface first with Nitro Thinner. Make sure the surface is dry.

To revive or change the color of the surface, apply two coats of Tutto Legno H2O Impregnante in the same color.

Dilute the paint 10-12% by volume with pure water and apply a first coat. After about 24 hours, lightly sand the surface to remove the wood grain and apply a second finishing coat, diluted 10-12% by volume with pure water.

For best results, apply the paint first horizontally and then vertically.

### USEFUL WARNINGS

- Do not apply at temperatures below +5°C, above +30°C, or with humidity above 75%.
- Use water to clean tools.
- For information on proper disposal, storage, and handling of the product, please consult the relevant safety data sheet.
- The product should be used preferably within two years of the production date if stored in the original, unopened containers and at appropriate temperatures.



#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## Tutto Legno Vernice H2O

Technical Data Sheet No. 142 - Revision 1 of 22/10/2013

<b>Binder nature</b>	Acrylic resin emulsion
<b>Specific gravity at 20°C</b>	1490 g/l +/- 50
<b>Flash point</b>	Non-flammable
<b>Dry film appearance</b>	Matte
<b>Apply with</b>	Brush, roller, airless
<b>Color</b>	Transparent
<b>Theoretical coverage</b>	10-12% with pure water
<b>Drying</b>	<b>Touch-safe:</b> 8 hours at 20°C
	<b>Dry-safe:</b> 48 hours at 20°C
<b>Overlay interval</b>	About 2 hours
<b>Dilution</b>	20-40% with pure water
<b>Tool Cleaning</b>	Immediately after use with water
<b>Packaging for Sale</b>	2.5 - 0.75 L
<b>Storage</b>	Store in a cool, dry place

### Specifications

Application of two coats of clear wood finish using a roller, brush, or airless sprayer on pre-treated wood.