



#Rives - #creativitàdecorativa
www.rives.it



Azienda certificata
UNI EN ISO 9001 - 14001

Acqua Repellent

Technical Data Sheet No. 160 - Revision 1 of 06/16/2022

Features and fields of application:

A water-repellent, protective, transparent-finish impregnator based on a water-based vinyl-versatate copolymer. Excellent performance and durability make it ideal for indoor application because it is completely solvent-free. ACQUA REPELLENT is ideal for waterproofing and protecting paint, thick coatings, Lecce stone, carparo stone, tuff, concrete, etc.

Substrate Preparation and Application:

The surface to be treated must be dry, cured, and free of dust or loose particles. Apply ACQUA REPELLENT diluted 200% by volume with pure water using a roller, brush, or airless sprayer. One or more coats, spaced 5-10 minutes apart, are recommended.



USEFUL WARNINGS

- Do not apply at temperatures below +5°C, above +30°C, or with humidity above 75%.
- Use water to clean tools.
- For information on proper disposal, storage, and handling of the product, please consult the relevant safety data sheet.
- The product should be used preferably within two years of the production date if stored in the original, unopened containers and at appropriate temperatures.



#Rives - #creativitàdecorativa
www.rives.it



Azienda certificata
UNI EN ISO 9001 - 14001

Acqua Repellent

Technical Data Sheet No. 160 - Revision 1 of 06/16/2022

Binder nature	Vinyl-versatate copolymer
Specific gravity at 20°C	1000 g/L +/- 50
Brookfield viscosity, 6 rpm, speed 20, 20°C	cP 1300
Flash point	non-flammable
Dry film appearance	opaque
Apply with	brush, roller, or airless
Color	clear
Theoretical coverage	10-12 m ² /L in two coats
Drying	To the touch: 30 minutes at 20°C
	To the depth: 48 hours at 20°C
Overlay interval	24 hours
Dilution	30-40% with pure water
Tool Cleaning	Immediately after use with water
Packaging for Sale	5-1 L
Storage	In a cool, dry place

Specifications

Application, with a brush, roller, or airless spray, of a transparent, glossy, water-based water repellent, suitable for protecting, waterproofing, and consolidating wall and stone surfaces.