



#Rives - #creativitàdecorativa
www.rives.it



Azienda certificata
UNI EN ISO 9001 - 14001

Ecosan Plus

Technical Data Sheet No. 108 - Revision 1 of 06/16/2022

Features and fields of application:

ECOSAN PLUS is a next-generation breathable, anti-mold, fungicidal, bactericidal, and sterilizing paint that's easy to apply to any surface, whether smooth or textured. Formulated to eliminate and prevent unsightly mold stains and to prevent the growth of microorganisms that provide a breeding ground for fungi, moss, and algae, Ecosan Plus gives surfaces a pleasant satin finish. It's particularly suitable for humid or poorly ventilated areas such as bathrooms, kitchens, and generally any environment where fungal contamination is a common and undesirable problem for health and hygiene reasons.



Substrate preparation:

New walls: Apply a coat of primer using our ALGA PRIMER diluted 200% with pure drinking water (1 liter of product and 2 liters of water).

Old walls: Remove all traces of dirt and ensure perfect adhesion of existing paint. On degraded surfaces with mold, algae, and moss, we recommend repairing, leveling, and smoothing with our RASOSTUCCO and remediating with our BLOCCAMUFFA internal biocidal cleaning solution. Once the surface is dry, sand, remove any residual dust, and then follow the same procedure as for new walls.

Apply a first coat of ECOSAN PLUS diluted 35-40% with potable water using a brush or roller. After 6 hours at 20°C, apply a second coat of the product diluted 30-35% with potable water.

USEFUL WARNINGS

- Do not apply at temperatures below +5°C, above +30°C, or with humidity above 75%.
- Use water to clean tools.
- For information on proper disposal, storage, and handling of the product, please consult the relevant safety data sheet.
- The product should preferably be used within two years from the production date if stored in the original unopened containers and under adequate temperature conditions.



#Rives - #creativitàdecorativa
www.rives.it



Azienda certificata
UNI EN ISO 9001 - 14001

Ecosan Plus

Technical Data Sheet No. 108 - Revision 1 of 06/16/2022

Binder nature	Acrylic emulsion
Specific gravity at 20°C	1650 g/L +/- 50
Brookfield viscosity, 6 rpm, speed 20, 20°C	cP 12600
Flash point	non-flammable
Dry film appearance	matt
Apply with	brush - roller
Color	white or "Interior Colors" color chart
Theoretical coverage	5-6 m ² /L in two coats
Drying	Touch dry: 2 hours at 20°C
	Dry dry: 24 hours at 20°C
Overlay interval	After approximately 24 hours
Dilution	30-40% with pure water
Tool Cleaning	Immediately after use with water
Packaging for Sale	L 14-5-2.5
Storage	In a cool, dry place

Specifications

Application, by roller or brush, of a breathable, anti-mold water-based paint on interior wall surfaces using a two-coat application cycle.