



#Rives - #creativitàdecorativa
www.rives.it



Azienda certificata
UNI EN ISO 9001 - 14001

Maxismalto

Technical Data Sheet No. 149 - Revision 1 of 06/16/2022

Features and areas of application:

Multipurpose synthetic enamel for interior and exterior use, offering excellent brushability and gloss, strong adhesion, good flexibility, excellent flow, and weather resistance.

Substrate preparation and application:

New surfaces: sand to remove any impurities and then degrease with thinner. For added protection, we recommend using our Rust Remover.

Damaged or previously painted iron surfaces: remove all traces of paint with a suitable paint stripper, thoroughly sand any rust-corroded areas. For added protection, we recommend using our Rust Remover.

Mix the product thoroughly, dilute it 8-10% with white spirit, and apply two coats with a brush, roller, or airless sprayer, waiting approximately 12 hours between coats.



USEFUL WARNINGS

- Do not apply at temperatures below +5°C, above +30°C, or with humidity above 75%.
- Use nitro thinner to clean tools.
- For information on proper disposal, storage, and handling of the product, please consult the relevant safety data sheet.
- The product should be used preferably within two years of the production date if stored in the original, unopened containers and at the appropriate temperature.
- The product is flammable and packaged in suitable packaging.
- The product should be kept away from open flames and sparks, in a cool, frost-free place, in its original, tightly closed containers.



#Rives - #creativitàdecorativa
www.rives.it



Azienda certificata
UNI EN ISO 9001 - 14001

Maxismalto

Technical Data Sheet No. 149 - Revision 1 of 06/16/2022

Binder nature	Alkyd and polyurethane resins
Specific gravity at 20°C	1.157 kg/L +/- 0.2 at 25°C
Brookfield viscosity, 6 rpm, speed 20, 20°C	cP 15600
Flash point	non-flammable
Dry film appearance	gloss
Apply with	brush, roller
Color	white or "Exterior Colors" color chart
Theoretical coverage	9-10 m ² /L per coat
Drying	Touch dry: 40 minutes at 20°C
	Dry dry: 24 hours at 20°C
Overlay interval	24 ore circa
Dilution	8-10% with pure water
Tool Cleaning	immediately after use with mineral spirits
Packaging for Sale	14 - 4 L
Storage	in a cool, dry place

Specifications

Application of marine plastic coating on exterior wall surfaces using a roller, brush, or airless spray, using a two-coat application cycle.