



#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## Opasint

Technical Data Sheet No. 153 - Revision 1 of 06/16/2022

### Features and fields of application:

High-coverage, matte synthetic primer. It offers high resistance, good flow, and easy sanding. Particularly suitable as a primer for wooden items, lacquers, windows, and interior and exterior walls.

Substrate preparation and application:

**New surfaces:** Fill any cracks or depressions in the wood with our FONDOSTUCK.

**Old or previously painted surfaces:** Remove all traces of paint with a suitable paint stripper, sand thoroughly, and proceed with the same procedure as for new surfaces.

Once dry, sand and apply a coat of OPASINT diluted 5-10% by volume with white spirit. After 6-12 hours, sand and apply a second coat of OPASINT diluted 10-15%. Finally, sand with fine sandpaper and apply two or more coats of topcoat.



### USEFUL WARNINGS

- Do not apply at temperatures below +5°C, above +30°C, or with humidity above 75%.
- Use nitro thinner to clean tools.
- For information on proper disposal, storage, and handling of the product, please consult the relevant safety data sheet.
- The product should be used preferably within two years of the production date if stored in the original, unopened containers and at suitable temperatures.



#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## Opasint

Technical Data Sheet No. 153 - Revision 1 of 06/16/2022

<b>Binder nature</b>	Alkyd urethane resins
<b>Specific gravity at 20°C</b>	1.50 g/l +/- 50
<b>Flash point</b>	non-flammable
<b>Dry film appearance</b>	matte
<b>Apply with</b>	brush, airless
<b>Color</b>	white
<b>Theoretical coverage</b>	10-12 m <sup>2</sup> /L per coat
<b>Drying</b>	<b>To the touch:</b> 8 hours at 20°C
	<b>To the depth:</b> 24 hours at 20°C
<b>Overlay interval</b>	Approximately 12 hours
<b>Dilution</b>	10-15% with white spirit
<b>Tool Cleaning</b>	Immediately after use with nitro thinner
<b>Packaging for Sale</b>	2.5 L – 0.500
<b>Storage</b>	In a cool, dry place

### Specifications

Application, by brush or airless, on pre-prepared surfaces, of one or two coats of high-coverage, matte synthetic primer.