



#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## Protector

Technical Data Sheet No. 400 - Revision 1 of 03/30/2010

### Features and fields of application:

A protective, solvent-based, glossy exterior impregnator, suitable for waterproofing and consolidating stone substrates and wall surfaces.

Penetrates pores without blocking breathability.

### Substrate preparation and application:

The surface to be treated must be dry, cured, and free of dust or loose particles.

Apply PROTECTOR undiluted, generously to the entire surface to be treated, using a soft brush or spray gun.

Spread the product from top to bottom. On very porous surfaces, a second coat is necessary.



### USEFUL WARNINGS

- Do not apply when ambient temperatures are below +5°C or above +30°C.
- Do not apply to very hot surfaces.
- Do not apply to frozen or wet surfaces.
- Use white spirit to clean tools.
- Avoid contact with eyes.
- Highly flammable.
- Store locked up and out of reach of children.
- Harmful by inhalation and in contact with skin. Irritating to skin.
- Do not dispose of residues in sewers.
- Do not use indoors.



#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## Protector

Technical Data Sheet No. 400 - Revision 1 of 03/30/2010

<b>Binder nature</b>	Acrylic resin
<b>Specific gravity at 20°C</b>	940 g/l +/- 50
<b>Dry film appearance</b>	gloss
<b>Apply with</b>	brush, airless
<b>Color</b>	colorless
<b>Theoretical coverage</b>	3-6 m <sup>2</sup> /L in two coats
<b>Drying</b>	<b>Touch dry:</b> 3 hours at 20°C
	<b>Dry dry:</b> 24 hours at 20°C
<b>Overlay interval</b>	About 12 hours
<b>Dilution</b>	Ready to use
<b>Tool Cleaning</b>	Immediately after use with mineral spirits
<b>Packaging for Sale</b>	14 L - 5 - 0.750
<b>Storage</b>	Store in a cool, dry place

### Specifications

#### COLORLESS SOLVENT-BASED PROTECTOR

Application of one or more coats of colorless, water-repellent waterproofing, suitable for protecting substrates requiring a certain level of gloss.