



#Rives - #creativitàdecorativa
www.rives.it



Azienda certificata
UNI EN ISO 9001 - 14001

Quick Paint T3D

Technical Data Sheet No. 181 - Revision 1 of 06/16/2022

Features and fields of application:

Breathable and washable water-based paint with a high whiteness.

Easy to apply, with good coverage and filling power. Thanks to its special formulation based on microparticles and selected aggregates, the product guarantees a film with excellent washability, breathability, and water repellency. Quick Paint T3D is particularly suitable for masking any plaster imperfections.



Substrate preparation and application:

New walls: ensure the substrate is at least four weeks old; clean thoroughly, removing all traces of dust or grease; ensure the surface is perfectly dry, apply a coat of our FISSATIVO R2000 primer and let dry.

Old walls: remove any small traces of dirt and ensure perfect adhesion of existing paint. On degraded substrates with mold, algae, and moss, we recommend repairing, leveling, and skimming with our RIVESTUCCO and remediating with our FISSATIVO R2000 primer. BLOCCAMUFFA, internal biocidal cleaning solution. Once the surface is dry, sand it, remove any residual dust, and then repeat the same procedure as for new walls.

On particularly chalky surfaces, we recommend using our M3000 insulating and consolidating impregnator as a primer. Mix the product thoroughly, dilute it 25-30% by volume with pure water, stir thoroughly, and apply using a roller or brush. After 3-6 hours at 20°C, apply a second coat, diluting the product 20-25% by volume with pure water.

USEFUL WARNINGS

- Do not apply at temperatures below +5°C, above +30°C, or with humidity above 75%.
- Use water to clean tools.
- For information on proper disposal, storage, and handling of the product, please consult the relevant safety data sheet.
- The product should preferably be used within two years from the production date if stored in the original unopened containers and under adequate temperature conditions.



#Rives - #creativitàdecorativa
www.rives.it



Azienda certificata
UNI EN ISO 9001 - 14001

Quick Paint T3D

Technical Data Sheet No. 181 - Revision 1 of 06/16/2022

Binder nature	Acrylic emulsion
Specific gravity at 20°C	1760 g/L +/- 50
Brookfield viscosity, 6 rpm, speed 20, 20°C	12,000 to 18,000 cP
Flash point	Non-flammable
Dry film appearance	Matt
Apply with	Brush, roller, or spray
Color	White
Theoretical coverage	4-5 m ² /L in two coats
Drying	Touch dry: 2 hours at 20°C
	Dry dry: 24 hours at 20°C
Overlay interval	About 12 hours
Dilution	30-40% with pure water
Tool Cleaning	Immediately after use with water
Packaging for Sale	L 14-4
Storage	In a cool, dry place

Specifications

Application by brush, roller, or airless spray of breathable, washable, acrylic resin-based water-based paint on interior surfaces using a two-coat application cycle.