



#Rives - #creativitàdecorativa
www.rives.it



Azienda certificata
UNI EN ISO 9001 - 14001

Quick Paint T45

Technical Data Sheet No. 122 - Revision 1 of 06/16/2022

Features and fields of application:

Breathable water-based paint for interior use based on vinyl resins in a water-based emulsion. Easy to apply, excellent dilutability, good coverage, and good coverage. The result is a soft, full, breathable film that tends to mask any imperfections in the substrate.

Substrate preparation and application:

New walls: ensure the substrate is at least four weeks old; clean thoroughly, removing all traces of dust or grease; ensure the surface is perfectly dry, apply a coat of our FISSATIVO R2000 primer, and let it dry.

Old walls: remove any small traces of dirt and ensure the perfect adhesion of existing paint. On degraded substrates with the presence of mold, algae, and moss, we recommend repairing, leveling, and skimming with our RASOSTUCCO and treating with our BLOCCAMUFFA, an internal biocidal cleaning solution. Once the substrate is dry, sand, remove any residual dust, and then repeat the same procedure as for new walls.

On particularly chalky substrates, we recommend using our M3000 insulating and consolidating primer.

Mix the product thoroughly, dilute it 25-30% by volume with pure water, stir thoroughly, and apply using a roller or brush. After 3-6 hours at 20°C, apply a second coat, diluting the product 20-25% by volume with pure water.

USEFUL WARNINGS

- Do not apply at temperatures below +5°C or above +30°C, or with humidity above 75%.
- Use water to clean tools.
- For information on proper disposal, storage, and handling of the product, please consult the relevant safety data sheet.
- The product should be used preferably within two years of the production date if stored in the original, unopened containers and at suitable temperatures.





#Rives - #creativitàdecorativa
www.rives.it



Azienda certificata
UNI EN ISO 9001 - 14001

Quick Paint T45

Technical Data Sheet No. 122 - Revision 1 of 06/16/2022

Binder nature	Vinyl emulsion
Specific gravity at 20°C	1740 g/L +/- 50
Brookfield viscosity, 6 rpm, speed 20, 20°C	12,000 to 22,000 cP
Flash point	Non-flammable
Dry film appearance	Matt
Apply with	Brush, roller, or spray
Color	White
Theoretical coverage	4-5 m ² /L in two coats
Drying	Touch dry: 2 hours at 20°C
	Dry dry: 24 hours at 20°C
Overlay interval	Approximately 12 hours
Diluizione	25-30% with pure water
Lavaggio attrezzi	Immediately after use with water
Confezioni in vendita	L 14-4
Stoccaggio	In a cool, dry place

Specifications

Application by brush, roller, or airless spray of breathable, vinyl-resin-based water-based paint on interior surfaces using a two-coat application cycle.