



#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## Tutto Legno Impregnating

Technical Data Sheet No. 152 - Revision 0 of 22/10/2013

### CHARACTERISTICS AND FIELDS OF USE

A protective, decorative, and transparent wood stain that penetrates deep into the wood's pores, highlighting its grain without forming a film. Its powerful penetrating action protects the wood from the elements and ultraviolet rays, while also providing effective woodworm and fungicide protection. It is free of waxy or similar compounds and does not affect the adhesion of any overpainting.

### SUBSTRATE PREPARATION AND APPLICATION

**New wood:** sand the surface and remove dust and dirt;

if using resinous wood, clean the surface beforehand. **New wood:** sand the surface and remove dust and dirt; if using resinous wood, clean the surface beforehand with Nitro Thinner; ensure the surface is dry.

Previously painted wood: remove all traces of dust, grease, wax residue, or old paint. Sand the surface and remove dust and dirt; if using resinous wood, clean the surface beforehand with Nitro Thinner; ensure the surface is dry.

Apply two coats of varnish as is, or, if necessary, diluted 5% with white spirit, trying to spread it in the direction of the wood grain.

### USEFUL WARNINGS

- Do not apply at temperatures below +5°C, above +30°C, or with humidity above 75%.
- Use water to clean tools.
- For information on proper disposal, storage, and handling of the product, please consult the relevant safety data sheet.
- The product should be used preferably within two years of the production date if stored in the original, unopened containers and at suitable temperatures.





#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## Tutto Legno Impregnating

Technical Data Sheet No. 152 - Revision 0 of 22/10/2013

<b>Binder nature</b>	Urethaneized alkyd resins
<b>Specific gravity at 20°C</b>	0.900 g/l +/- 50
<b>Dry film appearance</b>	Matt
<b>Apply with</b>	Brush, airless, immersion
<b>Color</b>	Color chart
<b>Theoretical coverage</b>	5-6 m <sup>2</sup> /L in two coats
<b>Drying</b>	<b>Touch-safe:</b> 8 hours at 20°C
	<b>Dry-safe:</b> 24 hours at 20°C
<b>Intervallo di sovrapplicazione</b>	About 12 hours
<b>Dilution</b>	20-40% with pure water
<b>Tool Cleaning</b>	Immediately after use with water
<b>Packaging for Sale</b>	2.5 - 0.75 L
<b>Storage</b>	Store in a cool, dry place

### Specifications

Application of a transparent or colored protective wood stain using a brush, airless spray, or immersion method, using a two-coat application cycle, on previously primed wood.