



#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## Tutto Legno Paint

Technical Data Sheet No. 151 - Revision 0 of 22/10/2013

### CHARACTERISTICS AND FIELDS OF USE

Glossy, transparent, and colored urethane varnish for interior and exterior use with a compact, hard, and durable finish. Suitable for all types of wood, it enhances the grain, providing high gloss and remarkable resistance to water and UV rays.

### SUBSTRATE PREPARATION AND APPLICATION

**New wood:** Sand the surface and remove dust and dirt; for resinous woods, clean the surface first with Nitro Thinner; make sure the surface is dry.

**Previously painted wood:** Remove all traces of dust, grease, wax residue, or old paint. Sand the surface and remove dust and dirt; for resinous woods, clean the surface first with Nitro Thinner; make sure the surface is dry.

Dilute the varnish 10-12% by volume with synthetic thinner or white spirit and apply a first coat. After approximately 48 hours, lightly sand the surface to remove the wood grain and apply a second finishing coat, diluted 5-10% by volume with synthetic thinner or white spirit.

For best results, apply the paint first horizontally and then vertically.



### USEFUL WARNINGS

- Do not apply at temperatures below +5°C, above +30°C, or with humidity above 75%.
- Use water to clean tools.
- For information on proper disposal, storage, and handling of the product, please consult the relevant safety data sheet.
- The product should be used preferably within two years from the production date if stored in the original, unopened containers and at appropriate temperatures.



#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## Tutto Legno Paint

Technical Data Sheet No. 151 - Revision 0 of 22/10/2013

<b>Binder nature</b>	Phenolic-modified alkyd resins
<b>Specific gravity at 20°C</b>	0.92 g/l +/- 50
<b>Dry film appearance</b>	gloss
<b>Apply with</b>	brush, roller, airless
<b>Color</b>	clear
<b>Theoretical coverage</b>	10-12 m <sup>2</sup> /L in two coats
<b>Drying</b>	<b>Touch-resistant:</b> 8 hours at 20°C
	<b>Dry-resistant:</b> 58 hours at 20°C
<b>Overlay interval</b>	Approximately 24 hours
<b>Dilution</b>	20-40% with pure water
<b>Tool Cleaning</b>	Immediately after use with water
<b>Packaging for Sale</b>	2.5 - 0.75 L
<b>Storage</b>	Store in a cool, dry place

### Specifications

Application of two coats of clear gloss wood varnish using a roller, brush, or airless sprayer on pre-treated wood.