



#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## R2000

Technical Data Sheet No. 136 – Revision 1 dated 16/06/2022

### Characteristics and areas of use:

Water-based acrylic styrene insulating fixative with penetrating and impregnating action. Highly concentrated, it consolidates powdery walls, seals absorbent surfaces, and anchors existing old paint layers. Suitable for the treatment of both old and new walls; it evens out surface absorbency and therefore improves the adhesion of the finishing coat.

### Substrate preparation and application:

**New walls:** ensure that the substrate has cured for at least four weeks; clean thoroughly, removing all traces of dust or grease; check that the surface is perfectly dry.

**Old walls:** remove any traces of dirt and ensure perfect adhesion of the existing paint. On deteriorated substrates with the presence of mold, algae, or moss, it is recommended to repair, level, and skim-coat with our \*Rasostucco\*, then carry out a sanitizing treatment with our \*Bloccamuffa\* or \*Alga Muschio Stop\*, biocidal washing solutions (for interior and exterior use respectively).

Once the substrate is dry, sand the surface, remove all dust residues, and then follow the same procedure as for new walls. Dilute \*Fissativo R2000\* 500% by volume with clean water and apply it with a roller or brush to the surface to be treated.

### USEFUL WARNINGS

- Do not apply at temperatures below +5°C or above +30°C, or with humidity above 75%.
- Use water to clean tools.
- For information regarding proper disposal, storage, and handling of the product, please consult the relevant safety data sheet.
- The product should preferably be used within two years from the date of manufacture if stored in its original, unopened containers and under suitable temperature conditions.





#Rives - #creativitàdecorativa  
www.rives.it



Azienda certificata  
UNI EN ISO 9001 - 14001

## R2000

Technical Data Sheet No. 136 – Revision 1 dated 16/06/2022

<b>Binder nature</b>	Styrene-acrylic emulsion
<b>Specific gravity at 20°C</b>	1000 g/l +/- 50
<b>Viscosity: Brookfield, 6 rpm, 20 rpm, 20°C</b>	cP 2000
<b>Flash point</b>	non-flammable
<b>Dry film appearance</b>	matte/gloss
<b>Apply with</b>	brush, roller
<b>Color</b>	colorless
<b>Theoretical coverage</b>	18-20 m <sup>2</sup> /L per coat
<b>Drying time</b>	<b>Touch-safe:</b> 8 hours at 20°C
	<b>Dry-safe:</b> 24 hours at 20°C
<b>Overcoating interval</b>	Approximately 5 hours
<b>Dilution</b>	500% by volume with pure water
<b>Tool cleaning</b>	Immediately after use with water
<b>Packaging available</b>	L 10-5-1
<b>Storage</b>	In a cool, dry place

### Specifications

Application by roller, brush, or airless spray of a solvent-free, water-based enamel on previously treated surfaces, ideal for indoor use with a two-coat application cycle.