#Rives - #creativitàdecorativa
www.rives.it

Azienda certificata
UNI EN ISO 9001 - 14001

Rives Gum

Technical Data Sheet No. 164 - Revision 2 dated May 3, 2023



Characteristics and Fields of Application:

Elastomeric liquid membrane with a protective finish, used to protect and waterproof exterior surfaces exposed to the most adverse environmental conditions. RIVES GUM, with its special formulation based on premium resins additivated with hydrophobic fillers, has an elastic appearance, excellent water-repellency power, excellent frost resistance, and adheres perfectly to various substrates such as terraces, roofs, cement agglomerates, floors, old bituminous membranes, etc. Also suitable in the presence of minor cracks caused by natural settling.

Surface Preparation and Application:

New surfaces: clean thoroughly by removing any traces of dust and grease, check that the surface is completely dry, apply a coat of our FISSATIVO R2000, a water-based styrene-acrylic sealer.
Old surfaces or surfaces already treated with other membranes: Remove every trace of dirt and ensure perfect adhesion of pre-existing paints. If necessary, repair and level any imperfections. Once the substrate is dry, remove any dust residue and apply a coat of our PLIOPRIMER, a solvent-based sealer

Application:

Dilute the product by 20-25% by volume with pure water. Apply two coats of product using a roller or brush, with a 24-hour interval between coats at 20°C.

Useful Warnings

- Do not apply at temperatures below +5°C, above +30°C, or with humidity above 75%.
- Use water to clean tools.
- For information regarding the proper disposal, storage, and handling of the product, please consult the relevant safety data sheet.
- The product should preferably be used within two years from the production date if stored in original, unopened containers under appropriate temperature conditions.

Rives s.r.l. Colors & Decorations - SP17 Salice - Veglie km1 - 73015 - Salice Salentino (LE) - Italia
Phone : + 39 0832 731655 - Fax : +39 0832 733467 - e-mail : rives@rives.it
www.rives.it - rives@pec.it - marketing@rives.it

#Rives - #creativitàdecorativa
www.rives.it

Azienda certificata
UNI EN ISO 9001 - 14001

Rives Gum

Technical Data Sheet No. 164 - Revision 2 dated May 3, 2023

Binder nature	Elastomeric emulsion
Specific gravity at 20°C	1460 g/L +/- 50
Brookfield viscosity spindle 6, speed 20, 20°C	14,000 to 18,000 cP
Dry film appearance	Matte
Application method (Apply with)	Brush or roller
Color	White, gray
Coverage (m²/L)	4–5 m²/L in two coats
Pack sizes (L)	14 L - 4 L - 0.75 L
Drying	**Touch dry:** 4 hours at 20°C
	Overcoating: 24 hours at 20°C
	Through-dry: 48 hours at 20°C
Dilution	20-25% with pure water
Tool cleaning	Immediately after use with water
Stoccaggio	In a cool and dry place

Voce di capitolato
Applicazione, a rullo o pennello, su terrazze, tetti e superfici esterne, di guaina elastomerica impermeabilizzante con ciclo applicativo a due mani.

Rives s.r.l. Colors & Decorations - SP17 Salice - Veglie km1 - 73015 - Salice Salentino (LE) - Italia
Phone : + 39 0832 731655 - Fax : +39 0832 733467 - e-mail : rives@rives.it
www.rives.it - rives@pec.it - marketing@rives.it